



# PRODUCT BULLETIN

## S.O.S. SEALER

(STAR OIL SPOT SEALER - LATEX BASED)

**S.O.S. Sealer** grabs and seals the oil and grease spots on all types of asphaltic surfaces.

The polymeric matrix and select surfactants in **S.O.S. Sealer** result in a tough film that bonds aggressively to the oil spot, to offer a sound surface for the subsequent seal coating.

### ADVANTAGES



- \* Dries quickly; in about 20 - 30 minutes
- \* Will stop oil from bleeding into the cured film of the seal coat
- \* Will not disbond from the oil spot.
- \* will not allow the sealer to peel away from primed areas
- \* Is water-based; ease in application, handling and clean-up

### SPECIFICATIONS AND DATA

**Dilution Rate:** One (1) Gallon of **S.O.S. Sealer** with Two (2) Gallons of clean potable water.

**Coverage Rate:** Approximately 175 - 200 sq. yards per gallon of the **S.O.S. Sealer** concentrate.

**Method of Application:** Brush, Roller or Spray.

**Surface Preparation:** Remove all loose dirt & scrape-off any heavy build-up of oil and grease.

Hose off and let dry. Apply the pre-diluted **S.O.S. SEALER** with a suitable applicator.

Do not apply, if rain is imminent within 8 hours or the ambient/surface temperature below 50 degrees F.

Precautions: Keep from freezing. **KEEP OUT OF REACH OF CHILDREN.**

Packaging: 5 Gallon plastic pails